






Ground Bar

Without Disconnecting Link

NEW



Code No.	No. of Terminal	Dimensions (mm)			Weight (kg)
		L	W	H	
GBDL 40	4	300	90	90	1.20
GBDL 60	6	400	90	90	1.52
GBDL 80	8	500	90	90	1.90
GBDL 100	10	650	90	90	2.37
GBDL 120	12	750	90	90	2.86
GBDL 140	14	850	90	90	3.24
GBDL 160	16	950	90	90	3.62
GBDL 180	18	1050	90	90	4.00
GBDL 200	20	1200	90	90	4.57
GBDL 220	22	1300	90	90	4.95
GBDL 240	24	1400	90	90	5.33
GBDL 260	26	1500	90	90	5.71
GBDL 280	28	1600	90	90	6.10
GBDL 300	30	1700	90	90	6.48



Material
Busbar – Tin Plated Copper – BS EN 13601
Support – Zinc Plated Steel with Insulator Bolt M8 – Stainless Steel. All the above products consist of 50x6 mm copper bar. Fix using wood screws 1½" x no.10



Tested Standard
IEC 62561 Part 1
TIS 3024 Part 1



Application
Suitable for bonding and testing point in grounding system.

Note : Special Size Length can be requested.

Disconnecting Link

Code No.	Dimensions (mm)			Weight (kg)
	L	W	H	
GBDL 253	125	90	90	0.91



Material
Tin Plated Copper Bar – BS EN 13601
Support – Zinc Plated Steel with Insulator STUD M8 – Stainless Steel. All the above products consist of 50x6 mm copper bar. Fix using wood screws 1½" x no.10



Tested Standard
IEC 62561 Part 1
TIS 3024 Part 1



Application
Suitable for bonding and testing point in grounding system.